THREE PHASE INDUCTION MOTOR

TYPE ⇨TOTALLY ENCLOSED FAN COOLED



DETAIL OF "Q"

DETAILED OF SHAFT END DRIVE

NOTE

1. 3 PHASE SQUIRREL CAGE INDUCTION MOTOR
2. PAINT COLOR : GRAY
3. ALL DIMENSIONS ARE IN MILLIMETERS.
4. THE TOLERANCE FOR THE "CENTER HEIGHT" ($^{0}_{-0.5}$)

NO	FRAME NO.	kW	POLE	VOLTS	HZ	INS. CLASS	SERVICE FACTOR	RATING	BEARINGS		APPROX WEIGHT	PROTECTION	MODEL NAME
									DRIVE	OPP.DRAVE			
A	112S	2.2	4	220/380	60	B	1.0	CONT.	6207ZZ	6205ZZ	32KG	IP44	103HK1DUS
B													
C													
D													

OTHER SPECIAL FEATURES

<참고>

1. MOTOR의 진동은 V30이하
2. ( )의 치수는 후가 공전 치수임

DRAWING NO.	

PREPEARED	CHECKED	APPROVED
2000.08.16 D.H.KAM	2000.08.16 H.J. KIM	2000.08.16 J.H. KIM

LG·OTIS